



Type

BERG NB1002V90 MOBI

Code

711A126



Self standing mobile unit
for cooling and dispensing beer

TECHNICAL DATA

| | |
|--|--|
| Compressor | 34,38 cc |
| Cooling power | 1750 W 6250 kJ/h |
| Continuing capacity | 166 l / 83 l |
| Temperature* | $\Delta t = 10^{\circ}\text{C}/20^{\circ}\text{C}$ |
| Ice bank | 33 kg = 11051 kJ |
| Cooling capacity 1. st hour | 459 l / 230 l |
| Water tank capacity | 70 l |
| Weight | 94,5 kg |
| Widht | 540 |
| Depth | 665 |
| Height | 1300 |

TECHNICAL SPECIFICATION

| | |
|-------------------|--------------------------|
| Refrigerant: | R134a |
| Evaporator: | Copper |
| Ref. System: | Capillary |
| Condenser: | Air - steel construction |
| Control type : | Mechanical |
| Circulation pump: | 7 m |
| Casing: | Stainless steel |
| Coils: | Beer 2x (8/7 x 20,5m) |

TECHNICAL EL. SPECIFICATION

| | |
|--------------------|-------------|
| Voltage/Frequency: | 230 V 50 Hz |
| Power: | 1,02 kW |
| Run: | 5,10 A |

All specifications (data) about compressors are based on: condensing temperature ($T_{\text{cond}}=55^{\circ}\text{C}$), evaporating temperature ($T_{\text{ev.}}=-5^{\circ}\text{C}$), ambient temperature ($T_{\text{amb.}}=32^{\circ}\text{C}$) and relative humidity $65\pm 5\%$.

All capacities and dispense rates are for 24°C Ambient, $15/24^{\circ}\text{C}$ beer ingoing and dispensing temperature $3-5^{\circ}\text{C}$.

OPREMA reserves the right to modify at any time the technical data and specifications reported herein, as the result of technical updating and improvement.